TEST VEHICLE INFORMATION


Vehicle Model Year and Make:
Vehicle Model and Body Style:
UPRIGHT POSITION DEGREES SEAT BACK SEAT CUSHION INCLINOMETER ADJUSTER
1. NOMINAL DESIGN RIDING POSITION
For adjustable driver and passenger seat backs, describe how to position the inclinometer to measure the seat back angle. Include description of the location of the adjustment latch detent if applicable.
Seat back angle for driver's seat = °.
Measurement Instructions:
Seat back angle for passenger's seat = $___^{\circ}$.
Measurement Instructions:

2. <u>SEAT FORE AND AFT POSITIONS</u>

Provide instructions for positioning the driver and front outboard passenger seat(s) in the center of fore and aft travel. For example, provide information to locate the detent in which the seat track is to be locked.

Position of the driver's seat:		
Position of the passenger's seat (if app	plicable):	

VEHICLE FUEL TANK ASSEMBLY



3. FUEL TANK CAPACITY DATA

3.1-A. "Usable Capacity" of standard equipment fuel tank = gallons.
B. "Usable Capacity" of optional equipment fuel tank = gallons.
C. Capacity used when certification testing to requirements of FMVSS 301 = gallons.
Operational Instructions:
3.2 Amount of Stoddard solvent added to vehicle for certification test = gallons.
3.3 Is vehicle equipped with electric fuel pump? YES NO If YES, does pump normally operate when vehicle's electrical system is activated? YES NO
STEERING COLUMN ASSEMBLY 2 1
LEFT SIDE VIEW

4. <u>STEERING COLUMN ADJUSTMENTS</u> Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes when it is moved through its full range of driving positions.

If the tested vehicle has any of these adjustments, does your company use any specific procedures to determine the geometric center.

Operational Instructions:

5. <u>SEATING REFERENCE POINT (SRP)</u>

Provide drawing which shows the driver's SRP location.

6. FUEL TANK LOCATION

Provide drawing which shows the undercarriage view of the vehicle.